

Learning to Use the Development Environment

Obviously you cannot program unless you understand how to create a file containing your C++ language source code, how to compile and link the source code to produce a program, how to execute (run) the program, test its behavior, fix errors, etc. For the first programming project, you will be given C++ source for a program that meets the specification given below. Your task is to type in the given source code, without making any unspecified modifications, and verify that it does indeed perform as specified. Along the way, you'll be exposed to quite a bit of C++ language that we haven't even begun to cover, so don't get paranoid. Try to understand the given source code (I've included lots of comments to help), but realize that this program uses elements of the C++ language from the first six sections of the class notes.

What to turn in and how:

This project will be submitted to the Automated Grader (EAGS). Instructions for submitting to EAGS are available from the EAGS homepage; see the link from the CS1044 webpage. The course notes also contain a tutorial for submitting an assignment. Be sure to follow those instructions carefully. In particular, do not alter the labels used in the sample output file below, and do not produce additional lines of output for aesthetic reasons.

This assignment will be worth 3% of your final grade. The assignment itself will be graded in two parts — correctness of output (90%) and style (10%). Style will be based upon inclusion of comments, spacing, and indentation as it appears in the given program. Neglecting comments, or left-justifying large portions of the code will result in deductions. A good effort to produce the code as written will suffice for this assignment.

The Program Specification:

Decision Making, Repeated Actions and File I/O:

theStarFleetPayroll

You are to write a very simple sort of payroll program, which will read data from a file, perform some arithmetic calculations, and write results in a nice tabular form to a file. The formats of the input and output files are described below, with examples. Be sure to pay careful attention to both.

Input file description and sample:

Your program **must** read its input from a file named `payroll-employees.dat` — use of another input filename will result in massive deductions. Each line of the input file will contain five values, separated by whitespace:

- Employee ID number (integer between 1000 and 9999)
- Employee's age (integer between 18 and 99)
- Employee's gross salary (real number between 0.00 and 9999.99)
- Insurance policy type (character — either B or D)
- Employee's name (character string ending at a newline)

You may assume that all input values will be logically correct (nonegatives, for instance), and that all values will be in the specified ranges. For instance:

3175	45	7597.43	B	McCoy, Leonard
5328	47	3000.00	D	Checkov, Pavel
3236	35	3897.89	B	Sulu, Hikaru
2334	49	2089.10	D	Riley, Kevin
5315	73	9336.00	B	Kirk, James
7641	58	5409.12	D	Uhura
7077	23	1001.00	B	Rand, Janice
4098	32	8594.98	D	Spock
3424	39	2999.99	B	Solo, Han
4297	52	1000.00	B	Chewbacca
1716	53	2011.50	D	Skywalker, Luke
5956	67	5245.42	D	Scott, Montgomery

Note that you must not make **any** assumptions about the number of lines of data in the input file. Your program must be written so that it will detect when it's out of input and terminate correctly (a technique for this will be presented in class).

What to Calculate:

You will write a program which computes the net monthly salary of each employee from his/her gross monthly salary. The deductions made on monthly gross salary are for insurance and taxes. The insurance fee paid by each employee is determined from the first table below. Each employee must also have amounts withheld for income and social security taxes according to his/her gross monthly income, at rates given in the second table:

Age	Monthly Insurance Cost	
	Basic	Deluxe
upto35	\$70	\$140
36to65	\$100	\$180
over65	\$150	\$250

Income Range	Income Tax Rate	Social Security Tax Rate
upto\$1000.00	15%	6.83%
\$1000.01 to \$3000.00	28%	6.83%
\$3000.01 and up	33%	6.83%

You must also calculate the average gross salary, average insurance fee, average income tax withheld, average social security tax withheld, and average net salary for all the employees for whom you are given data.

Output description and sample:

Your program must write output data to a file named `payola.dat` — use of any other output filename will result in a massivedeductionofpoints.

This sample output file shown below correspond to the input data given above:

Programmer: Chris Knestrick MacroSoft Corporation Payroll					
ID	Gross Pay	SSI	FIT	Ins	Net Pay
3175	7597.43	518.90	2227.15	100.00	4751.37
5328	3000.00	204.90	710.00	180.00	1905.10
3236	3897.89	266.23	1006.30	70.00	2555.36
2334	2089.10	142.69	454.95	180.00	1311.47
5315	9336.00	637.65	2800.88	150.00	5747.47
7641	5409.12	369.44	1505.01	180.00	3354.67
7077	1001.00	68.37	150.28	70.00	712.35
4098	8594.98	587.04	2556.34	140.00	5311.60
3424	2999.99	204.90	710.00	100.00	1985.09
4297	1000.00	150.00	68.30	100.00	681.70
1716	2011.50	137.39	433.22	180.00	1260.89
5956	5245.42	358.26	1450.99	250.00	3186.17
Avg:	4348.54	297.00	1179.59	141.67	2730.27

You are not required to use this exact horizontal spacing, but your output must satisfy the following requirements:

- All dollar amounts must be printed to show two places after the decimal.
- You must use the specified header, and column labels, and include your name in the first line as shown.
- You must arrange your output in neatly aligned columns, with a label identifying the contents of each column.
- You must show the required averages below the corresponding columns.
- You must use the same ordering of the columns as shown here.

Programming Standards:

You'll be expected to observe good programming/documentation standards. All the discussions in class about formatting, structure, and commenting your code will be enforced. A copy of *Elements of Programming Style* is included with the course notes — if you don't have a copy I strongly suggest you read the on-line edition (available from the course web page). Some specifics:

- You must include header comments specifying the compiler and operating system used and the date completed.
- You must include a comment explaining the purpose of every variable you use in your program.
- You must use meaningful, suggestive (of function or purpose!) variable names.
- Use named constants instead of variables where appropriate.
- Precede every major block of your code with a comment explaining its purpose. You don't have to describe how it works unless you do something so sneaky it deserves special recognition.
- You must use indentation to make control structures like loops and if-else statements more readable.

Hints:

This program requires that you know how to manage file-oriented input/output operations ---the slides and the text provide good examples and guidelines. You'll have to use **manipulators** to manage the formatting of your code. Read the discussion in the course notes carefully, there are important clues there.

You'll need to use if-then control structures extensively ---be sure to read Chapter 5 of the course notes. You'll also need to use some sort of loop control structure to manage reading and processing of input. That's covered in Chapter 6 of the course notes.

TheSourceCode:

```
////////////////////////////////////
// Identification
// (You should substitute the correct information in the following
// lines.)
//
// Title:           Simple Payroll Program
// Programmer:      Chris Knestrick
// ID Number:       999-99-9999
// Compiler:        Visual C++ version 6.0
// Platform:        Pentium II 400 / Windows NT
// Last Modified:   July 2, 2001
//
////////////////////////////////////
// Honor Pledge
//   On my honor:
//
//   - I have not discussed the C++ language code in my program with
//     anyone other than my instructor or the teaching assistants
//     assigned to this course.
//
//   - I have not used C++ language code obtained from another student,
//     or any other unauthorized source, either modified or unmodified.
//
//   - If any C++ language code or documentation used in my program
//     was obtained from another source, such as a text book or course
//     notes, that has been clearly noted with a proper citation in
//     the comments of my program.
//
//   - I have not designed this program in such a way as to defeat or
//     interfere with the normal operation of the Automated Grader.
//
////////////////////////////////////
// Purpose of the program:
//
// This program reads information about an arbitrary number of
// employees from an input file named "payroll-employees.dat":
//
//   - ID number
//   - age
//   - gross monthly salary
//   - insurance plan type
//
// and computes the correct deductions for:
//
//   - federal income tax
//   - social security tax
//   - insurance fee
//   - net monthly salary.
//
// It then prints out a labeled table of results, showing for
// each employee the ID number, gross salary, insurance fee,
// income and social security tax deductions and net salary.
// In addition, the averages of each category are computed and
// printed.  Output is is to a file named "payola.dat".
//
```

```
////////////////////////////////////
//
// The is the #include section. These statements tell the compiler
// to read and use variables and functions declared in the specified
// files.
#include <fstream.h>
#include <iomanip.h>

// Every C++ program must have a function named main. This is the
// beginning of the definition of the main function for this
// simple program. In this case the whole program consists of just
// the main function --- usually programs involve more than one
// function.
//
int main() {

// In this section, named constants are declared and given
// their values. We could just use the numbers themselves in the
// code that follows, but the names make the code more readable;
// the name SSRate carries meaning where the number 0.0683 doesn't.
//
const double HiTax = 0.33;           // income tax rates
const double MidTax = 0.28;
const double LoTax = 0.15;
const double SSRate = 0.0683;      // ssi tax rate

const double HiBasic = 150.00;     // insurance fees
const double MidBasic = 100.00;
const double LoBasic = 70.00;
const double HiDeluxe = 250.00;
const double MidDeluxe = 180.00;
const double LoDeluxe = 140.00;

const double HiIncome = 3000.00;   // income levels
const double MidIncome = 1000.00;

const char Basic = 'B';           // insurance plan type codes
const char Deluxe = 'D';

// In this section, the variables used in main() are declared.
// Each variable has a type (integer, double, etc) but no particular
// value at this point. The variable names like the constant names
// used above are supposed to be meaningful, and each declared
// variable is also given a short comment explaining what it will
// be used for.
//
ifstream inPay;                   // input file stream
ofstream outPay;                  // output file stream

int    IdNum,                     // employee ID number,
       Age,                       // age.
       NumEmployees;              // number of employees.
```

```
double GrossPay,      // employee gross pay.
       NetPay,        // net pay,
       SSI,           // SS tax,
       FIT,           // income tax,
       InsFee,        // insurance fee..
       TotalGross,    // total of all gross pay,
       TotalNet,      // net pay,
       TotalIns,      // insurance fees,
       TotalSSI,      // SSI tax,
       TotalFIT;      // income tax.

char   InsPlan;       // employee insurance plan

// This is the initialization section of main(). We must ensure
// every variable is given a value before it is used in a calculation
// or printed. Some variables get their values by being read from the
// input file, so they don't need to be initialized here.

NumEmployees = 0;     // Initialize counters and running totals
TotalGross   = 0.0;   // to zero.
TotalNet     = 0.0;
TotalIns     = 0.0;
TotalSSI     = 0.0;
TotalFIT     = 0.0;

// The following four statements prepare the input and output files
// for use. Don't worry too much about what's going on here just yet,
// we'll cover the details shortly.
//
inPay.open("payroll-employees.dat"); // open input and output files
outPay.open("payola.dat");
outPay.setf(ios::fixed, ios::floatfield);
outPay.setf(ios::showpoint);

// The following statements print the header info to output file. It's
// rather cryptic at this point, but you'll see output is really very
// simple in C++.

outPay << "Programmer: Chris Knestrick" << endl;
outPay << "StarFleet Payroll" << endl << endl;
outPay << "   ID   Gross Pay   FIT       SSI       Ins       Net Pay";
outPay << endl;
outPay << "=====";
outPay << endl;

// This statement tries to read first line of data from input file. If
// something goes wrong, the variable inPay will be false (small lie) and
// that will prevent us from going into the loop that follows and generating
// nonsense.

inPay >> IdNum >> Age >> GrossPay >> InsPlan;

// What comes next is a while loop. The body of the loop gets
// executed over and over again until the expression that follows
// the while (inPay in this case) becomes false. Therefore, we'd
// better be sure that inPay will eventually become false,
// otherwise the program will continue to execute the body of this
// loop forever.
```

```
while (inPay) {

    // The first part of the loop body (down to the comment with
    // all the hyphens) processes the data that was just read in.

    NumEmployees++;           // Count employees. This statement
                              // adds 1 to the value of the
                              // variable NumEmployees.
    TotalGross += GrossPay;   // Update total gross pay. This
                              // statement adds the value of
                              // the variable GrossPay to the
                              // variable TotalGross

    // The switch statement tries to match the value of the selection
    // variable (InsPlan this time) with the given cases. When a
    // match is found, the statements that accompany that case are
    // executed. If no match is found, the default case is carried out.

    switch (InsPlan) {        // Calculate insurance fees:
    case Basic:{ if (Age <= 35) // for Basic plan
                  InsFee = LoBasic; // This statement copies the
                                      // value of the constant
                                      // LoBasic to the variable
                                      // InsFee -- assignment.
                else if (Age <= 65)
                  InsFee = MidBasic;
                else
                  InsFee = HiBasic;
                break;
            }
    case Deluxe:{ if (Age <= 35) // for Deluxe plan
                  InsFee = LoDeluxe;
                  else if (Age <= 65)
                  InsFee = MidDeluxe;
                  else
                  InsFee = HiDeluxe;
                  break;
            }
    default :{ cout << "Employee " << setw(4) << IdNum;
               cout << " has invalid insurance plan." << endl;
               InsFee = 0.0;
            }
    }

    TotalIns += InsFee;       // Update total insurance fees.

    if (GrossPay <= MidIncome) { // Determine FIT amount.
        FIT = LoTax * GrossPay; // low income
    }
    else if (GrossPay <= HiIncome) {
        FIT = LoTax * MidIncome // middle income
              + MidTax * (GrossPay - MidIncome);
    }
    else {
        FIT = LoTax * MidIncome // high income
              + MidTax * (HiIncome - MidIncome)
              + HiTax * (GrossPay - HiIncome);
    }
    TotalFIT += FIT;         // Update total income taxes.
}
```

```
SSI = SSRate * GrossPay;           // Calculate SSI tax.
TotalSSI += SSI;                   // Update total SS taxes.

NetPay = GrossPay - InsFee -
        FIT - SSI; // Calculate net pay.
TotalNet += NetPay; // Update total net pay.

// This section of the loop body prints the results calculated
// above into the output file.

outPay << setw( 6) << IdNum;
outPay << setw(12) << setprecision(2) << GrossPay;
outPay << setw(10) << setprecision(2) << SSI;
outPay << setw(10) << setprecision(2) << FIT;
outPay << setw(10) << setprecision(2) << InsFee;
outPay << setw(12) << setprecision(2) << NetPay;
outPay << endl;

// ----- End of Processing Section

// This statement skips over the employee names to the beginning
// of the next line of input.

inPay.ignore(200, '\n');

// This statement tries to read the next line of input. This
// is the last statement in the loop body, so the next thing
// that will happen is that the loop control expression (inPay
// in this case) is tested.

inPay >> IdNum >> Age >> GrossPay >> InsPlan;

} // End of while loop.

// Once we've exited the loop, we're done reading and processing data for
// new employees. It's time to sum things up. The following statements
// print out the averages in a nice form. First print a line to mark
// the end of the table body:

outPay << "===== ";
outPay << endl;

// Now, calculate and print averages, if appropriate. We've got to be
// careful not to calculate averages if there weren't any employees, so
// this uses an if statement to be sure that's not the case before any
// dividing is done.
if (NumEmployees > 0) {
    outPay << " Avg:";
    outPay << setprecision(2);
    outPay << setw(12) << TotalGross/NumEmployees;
    outPay << setw(10) << TotalFIT/NumEmployees;
    outPay << setw(10) << TotalSSI/NumEmployees;
    outPay << setw(10) << TotalIns/NumEmployees;
    outPay << setw(12) << TotalNet/NumEmployees;
    outPay << endl;
}
```

```
// These two statements just close the input and output files; this
// tells the operating system that we're done with them and (hopefully)
// that the files are properly saved to disk.

    inPay.close();
    outPay.close();

// The return statement sends a value back to whoever called this
// function.  If you're using Visual C++, you may see this value
// displayed in the window at the bottom of the screen when you run
// the program.

    return NumEmployees;
}                                     // end of main()
```