

Chapter 2

Processes and Threads



Last lecture review

- Resource Descriptors
 - File
 - Process
- Process Vs Threads (more elaboration today)
- `fork()` Vs `exec()`



Process

- `Heavy-weight' unit of computation
- Process descriptor
 - Object program (Program text)
 - Data segment
 - Process Status Word (PSW) – executing, waiting, ready
 - Resources acquired




Thread

- Thread: light-weight process
 - OS maintains minimal internal state information
- Usually instantiated from a process
- Each thread has its OWN unique descriptor
 - Data, Thread Status Word (TSW)
- SHARES with the parent process (and other threads)
 - Program text
 - Resources
 - Parent process data segment

Process Vs Threads

- Processes require substantial more OS overhead in creation and maintenance



Taken from Modern Operating Systems, 2nd Ed, Tanenbaum, 2001



wait()

- Used by parent process to wait on ONE child process to finish
- `int wait(&status);`
- return value of wait is the process id of child process that just finished
- if no child processes, wait returns -1 immediately

wait() ... ctd

- wait returns value if child process
 - called function `exit()`... or terminated normally
 - gets terminated by a signal
- returns exit status of child in variable `status`



waitpid()


- Used by parent to wait on a specific child process to terminate indicated by pid
- `int waitpid(pid, &status, options)`
- `pid`: process id of the child process parent waits on



pipes

- One form of inter-process communication (IPC)
- follows message-passing paradigm of IPC

pipes....ctd



```
int fds[2];  
retval = pipe(fd);
```

- creates two file descriptors, one for reading, the second for writing



pipes...ctd

```
int fds[2]; char s[100];
retval = pipe(fds);
pid = fork();
if(pid != 0) { /* parent process */
    write(fds[1], "hello", 6);
}
else { /* child process */
    read(fds[0], s, 100);
    printf("Read %s\n", s);
}
```



What are pthreads?

- A standardized programming interface
- For UNIX systems, specified by the IEEE POSIX 1003.1c standard (1995).
- Implementations which adhere to this standard are referred to as POSIX threads, or Pthreads.

Why pthreads over fork()?

- Primary reason is performance gains
- Less OS overhead in creating a new thread
- All threads use same address space, so communication between threads is easier
- `$gcc -o firstthread firstthread.c -lpthread`



pthread creation

- Use `pthread_create` function

`pthread_create(thread, attr, routine, arg)`

- `thread`: Name of this thread
- `attr`: Thread attributes
- `routine`: function that gets executed once thread is started
- `arg`: A single argument to be passed to routine, cast as pointer of type void, passed by reference.
 - For multiple arguments, bundle them up in a struct and pass struct to routine



First pthread program

```
#include <pthread.h>
#include <stdio.h>
#define NUM_THREADS      5
int main()
{
    pthread_t threads[NUM_THREADS];
    int rc, t;
    for(t=0;t < NUM_THREADS;t++){
        printf("Creating thread %d\n", t);
        rc = pthread_create(&threads[t], NULL, PrintHello,
(void *)t);
    }
    pthread_exit(NULL);
}
```

First pthread program... ctd

```
void *PrintHello(void *threadid)
{
    printf("%d: Hello World!\n", threadid);
    pthread_exit(NULL);
}
```

- `pthread_exit(void *status)` : Used to explicitly terminate a thread
- Thread can use the `status` variable to specify its status; pass data to `joining' threads



pthread_s... ctd

- `pthread_join()` : Analogous to `wait()` for processes.
- Allows threads to `join` to form single thread of execution



Second example

```
#include <pthread.h>
#include <stdio.h>

int main(void) {
    int N = 8;
    pthread_t hThread;    int fact;
    pthread_create(&hThread, NULL, (void *)ChildThread,
        (void *)N);
    pthread_join(hThread, (void *)&fact);

    printf("Factorial of N = %d\n", fact); return 0;
}
```



Second example... ctd

```
void ChildThread(int N) {
    int i;  int fact = 1;

    for (i=1; i<=N; ++i)
        { fact*=i; }

    pthread_exit((void *) fact);
}
```



Reference for pthreads

- Posix threads programming

<http://www.llnl.gov/computing/tutorials/workshops/workshop/pthreads/MAIN.html#Pthread>

- Introduction to pthreads

<http://phoenix.liunet.edu/~mdevi/pthread/Intro.htm>