

# CS 3214, Fall 2011

## Project 2: The Buffer Bomb

### Due: Wednesday, September 21, 11:59PM

This project was developed by Randy Bryant; it was adapted for Virginia Tech by Godmar Back ([gback@cs.vt.edu](mailto:gback@cs.vt.edu)).

**Minimum requirement:** To obtain a passing grade in CS 3214, we expect that by the end of the semester your group was successful in igniting at least Level 2, which is the "Firecracker" phase of the bomb.

## Introduction

This assignment will help you develop a detailed understanding of IA-32 calling conventions and stack organization. It involves applying a series of *buffer overflow attacks* on an executable file `bufbomb` provided to you.

**Note:** In this project, you will gain firsthand experience with one of the methods commonly used to exploit security weaknesses in operating systems and network servers. Our purpose is to help you learn about the runtime operation of programs and to understand the nature of this form of security weakness so that you can avoid it when you write system or application code. We do not condone the use of this or any other form of attack to gain unauthorized access to any system resources. There are criminal statutes governing such activities.

## Logistics

You may work in a group of up to two people in solving the problems for this project. The only "hand-in" will be an automated logging of your successful attacks. Any clarifications and revisions to the project will be posted on the course web page.

We generated the buffer bomb executable using `gcc's -m32` flag, so all code produced by the compiler follows IA-32 rules, even if the host is an x86-64 system.

---

## Hand Out Instructions

You can obtain your buffer bomb by pointing your Web browser at:

```
http://courses.cs.vt.edu/~cs3214/fall2011/buflab/buflab-handout.tar
```

The server will return a `tar` file called `buflab-handout.tar` to your browser. Start by copying `buflab-handout.tar` to a (protected) directory in which you plan to do your work. It is okay for each group member to maintain a copy in their own respective directory. Then give the command `"tar xvf buflab-handout.tar"`. This will create a directory called `buflab-handout` containing the following three executable files:

**bufbomb:** The buffer bomb program you will attack.

**makecookie:** A utility that generates a "cookie" based on your teamid.

**hex2raw:** A utility to help convert between string formats.

In the following instructions, we will assume that you have copied the three programs to a protected local directory, and that you are executing them in that local directory.

## Team IDs and Cookies

Phases of this project will require a slightly different solution from each group. The correct solution will be based on your teamid. The teamid is the concatenation of your SLO IDs using a + in between. If you're in a group by yourselves, simply use your SLO ID. While the order of the two SLO IDs in a teamid does not matter, you must always choose the same ordering for the IDs. Teams `"rnikola+parang"` and `"parang+rnikola"` are considered distinct. **You must follow this scheme for generating your teamid. Our grading program will only give credit to those people whose SLO IDs can be extracted from the teamids.**

A *cookie* is a string of eight hexadecimal digits that is (with high probability) unique to your team id. You can generate your cookie with the `makecookie` program giving your teamid as the argument. For example:

```
unix> ./makecookie rnikola+parang
0x1005b2b7
```

In four of your five buffer attacks, your objective will be to make your cookie show up in places where it ordinarily would not.

## The BUFBOMB Program

The BUFBOMB program reads a string from standard input. It does so with the function `getbuf` defined below:

---

```
1 int getbuf()
2 {
3     char buf[NORMAL_BUFFER_SIZE];
4     Gets(buf);
5     return 1;
6 }
```

The function `Gets` is similar to the (long-deprecated) standard library function `gets`—it reads a string from standard input (terminated by `'\n'` or end-of-file) and stores it (along with a null terminator) at the specified destination. In this code, you can see that the destination is an array `buf` having sufficient space for 32 characters.

`Gets` (and `gets`) grabs a string off the standard input stream and stores it into its destination address (in this case `buf`). However, `Gets()` has no way of determining whether `buf` is large enough to store the whole input. It simply copies the entire input string, possibly overrunning the bounds of the storage allocated at the destination.

If the string typed by the user to `getbuf` is no more than 31 characters long, it is clear that `getbuf` will return 1, as shown by the following execution example:

```
unix> ./bufbomb -u rnikola+parang
Type string: I love CS3214.
Dud: getbuf returned 0x1
```

Typically an error occurs if we type a longer string:

```
unix> ./bufbomb -u rnikola+parang
Type string: It is easier to love this class when you are a TA.
Ouch!: You caused a segmentation fault!
```

As the error message indicates, overrunning the buffer typically causes the program state to be corrupted, leading to a memory access error. Your task is to be more clever with the strings you feed `BUFBOMB` so that it does more interesting things. These are called *exploit* strings.

`BUFBOMB` takes several different command line arguments:

`-u teamid`: Operate the bomb for the indicated teamid. You should always provide this argument for several reasons:

- It is required to submit your successful attacks to the grading server.
- `BUFBOMB` determines the cookie you will be using based on your teamid, as does the program `MAKECOOKIE`.
- We have built features into `BUFBOMB` so that some of the key stack addresses you will need to use depend on your teamid's cookie.

`-h`: Print list of possible command line arguments.

- 
- n: Operate in “Nitro” mode, as is used in Level 4 below.
  - s: Submit your solution exploit string to the grading server.

At this point, you should think about the x86 stack structure a bit and figure out what entries of the stack you will be targeting. You may also want to think about *exactly* why the last example created a segmentation fault, although this is less clear.

Your exploit strings will typically contain byte values that do not correspond to the ASCII values for printing characters. The program HEX2RAW can help you generate these *raw* strings. It takes as input a *hex-formatted* string. In this format, each byte value is represented by two hex digits. For example, the string “012345” could be entered in hex format as “30 31 32 33 34 35.” (Recall that the ASCII code for decimal digit  $x$  is  $0 \times 3x$ .)

The hex characters you pass HEX2RAW should be separated by whitespace (blanks or newlines). I recommend separating different parts of your exploit string with newlines while you’re working on it. HEX2RAW also supports C-style block comments, so you can mark off sections of your exploit string. For example:

```
b f 66 7b 32 78 /* mov      $0x78327b66,%edi */
```

Be sure to leave space around both the starting and ending comment strings (`/*, */`) so they will be properly ignored.

If you generate a hex-formatted exploit string in the file `exploit.txt`, you can apply the raw string to BUFBOMB in several different ways:

1. You can set up a series of pipes to pass the string through HEX2RAW.

```
unix> cat exploit.txt | ./hex2raw | ./bufbomb -u rnikola+parang
```

2. You can store the raw string in a file and use I/O redirection to supply it to BUFBOMB:

```
unix> ./hex2raw < exploit.txt > exploit-raw.txt
unix> ./bufbomb -u rnikola+parang < exploit-raw.txt
```

This approach can also be used when running BUFBOMB from within GDB:

```
unix> gdb bufbomb
(gdb) run -u rnikola+parang < exploit-raw.txt
```

### Important points:

- Your exploit string must not contain byte value `0x0A` at any intermediate position, since this is the ASCII code for newline (`'\n'`). When `Gets` encounters this byte, it will assume you intended to terminate the string.

- 
- HEX2RAW expects two-digit hex values separated by a whitespace. So if you want to create a byte with a hex value of 0, you need to specify 00. To create the word 0xDEADBEEF you should pass DE AD BE EF to HEX2RAW.

When you have correctly solved one of the levels, say level 0:

```
../hex2raw < smoke-rnikola+parang.txt | ../bufbomb -u rnikola+parang
Userid: rnikola+parang
Cookie: 0x1005b2b7
Type string:Smoke!: You called smoke()
VALID
NICE JOB!
```

then can submit your solution to the grading server using the `-s` option:

```
../hex2raw < smoke-rnikola+parang.txt | ../bufbomb -u rnikola+parang -s
Userid: rnikola+parang
Cookie: 0x1005b2b7
Type string:Smoke!: You called smoke()
VALID
Sent exploit string to server to be validated.
NICE JOB!
```

The server will test your exploit string to make sure it really works, and it will update the Buffer Lab scoreboard page indicating that your teamid (listed by your cookie for anonymity) has completed this level.

You can view the scoreboard by pointing your Web browser at <http://courses.cs.vt.edu/~cs3214/fall2011/buflab/buflab-scoreboard.html>

Unlike the Bomb Lab, there is no penalty for making mistakes in this project. Feel free to fire away at BUFBOMB with any string you like. Of course, you shouldn't brute force this project either, since it would take longer than you have to do the assignment.

**IMPORTANT NOTE:** You can work on your buffer bomb on any Linux machine, but in order to submit your solution, you will need to be running on one of the machines that are part of the `rlogin.cs.vt.edu` cluster.

## Level 0: Candle 10 pts

The function `getbuf` is called within BUFBOMB by a function `test` having the following C code:

```
1 void test()
2 {
3     int val;
4     volatile int local = 0xdeadbeef;
```

---

```
5
6     val = getbuf();
7
8     /* Check for corrupted stack */
9     if (local != 0xdeadbeef) {
10         printf("Sabotaged!: the stack has been corrupted\n");
11     }
12     else if (val == cookie) {
13         printf("Boom!: getbuf returned 0x%x\n", val);
14         validate(3);
15     } else {
16         printf("Dud: getbuf returned 0x%x\n", val);
17     }
18 }
```

When `getbuf` executes its return statement (line 5 of `getbuf`), the program ordinarily resumes execution within function `test` (at line 7 of this function). We want to change this behavior. Within the file `bufbomb`, there is a function `smoke` having the following C code:

```
void smoke()
{
    printf("Smoke!: You called smoke()\n");
    validate(0);
    exit(0);
}
```

Your task is to get `BUFBOMB` to execute the code for `smoke` when `getbuf` executes its return statement, rather than returning to `test`. Note that your exploit string may also corrupt parts of the stack not directly related to this stage, but this will not cause a problem, since `smoke` causes the program to exit directly.

**Some Advice:**

- All the information you need to devise your exploit string for this level can be determined by examining a disassembled version of `BUFBOMB`. Use `objdump -d` to get this disassembled version.
- Be careful about byte ordering.
- You might want to use GDB to step the program through the last few instructions of `getbuf` to make sure it is doing the right thing.
- The placement of `buf` within the stack frame for `getbuf` depends on which version of GCC was used to compile `bufbomb`, so you will have to read some assembly to figure out its true location.

---

## Level 1: Sparkler 15 pts

Within the file `bufbomb` there is also a function `fizz` having the following C code:

```
void fizz(int val)
{
    if (val == cookie) {
        printf("Fizz!: You called fizz(0x%x)\n", val);
        validate(1);
    } else
        printf("Misfire: You called fizz(0x%x)\n", val);
    exit(0);
}
```

Similar to Level 0, your task is to get `BUFBOMB` to execute the code for `fizz` rather than returning to `test`. In this case, however, you must make it appear to `fizz` as if you have passed your `cookie` as its argument. How can you do this?

### Some Advice:

- Note that the program won't really call `fizz`—it will simply execute its code. This has important implications for where on the stack you want to place your `cookie`.

## Level 2: Firecracker 15 pts

A much more sophisticated form of buffer attack involves supplying a string that encodes actual machine instructions. The exploit string then overwrites the return pointer with the starting address of these instructions on the stack. When the calling function (in this case `getbuf`) executes its `ret` instruction, the program will start executing the instructions on the stack rather than returning. With this form of attack, you can get the program to do almost anything. The code you place on the stack is called the *exploit* code. This style of attack is tricky, though, because you must get machine code onto the stack and set the return pointer to the start of this code.

Within the file `bufbomb` there is a function `bang` having the following C code:

```
int global_value = 0;

void bang(int val)
{
    if (global_value == cookie) {
        printf("Bang!: You set global_value to 0x%x\n", global_value);
        validate(2);
    } else
        printf("Misfire: global_value = 0x%x\n", global_value);
    exit(0);
}
```

---

Similar to Levels 0 and 1, your task is to get BUFBOMB to execute the code for `bang` rather than returning to `test`. Before this, however, you must set global variable `global_value` to your teamid's cookie. Your exploit code should set `global_value`, push the address of `bang` on the stack, and then execute a `ret` instruction to cause a jump to the code for `bang`.

**Some Advice:**

- You can use GDB to get the information you need to construct your exploit string. Set a breakpoint within `getbuf` or `Gets` and run to this breakpoint. Determine parameters such as the address of `global_value` and the location of the buffer.
- Determining the byte encoding of instruction sequences by hand is tedious and prone to errors. You can let tools do all of the work by writing an assembly code file containing the instructions and data you want to put on the stack. Assemble this file with `gcc -m32 -c` and disassemble it with `objdump -d`. You should be able to get the exact byte sequence that you will type at the prompt. (A brief example of how to do this is included at the end of this writeup.)
- Keep in mind that your exploit string depends on your machine, your compiler, and even your teamid's cookie. You must do this project on the machines of the rlogin cluster. Make sure you include the proper teamid on the command line to BUFBOMB.
- Watch your use of address modes when writing assembly code. Note that `movl $0x4, %eax` moves the *value* `0x00000004` into register `%eax`; whereas `movl 0x4, %eax` moves the value *at* memory location `0x00000004` into `%eax`. Since that memory location is usually undefined, the second instruction will cause a segfault!
- Do not attempt to use either a `jmp` or a `call` instruction to jump to the code for `bang`. These instructions uses PC-relative addressing, which is very tricky to set up correctly. Instead, push an address on the stack and use the `ret` instruction.

## Level 3: Dynamite 20 pts

Our preceding attacks have all caused the program to jump to the code for some other function, which then causes the program to exit. As a result, it was acceptable to use exploit strings that corrupt the stack, overwriting saved values.

The most sophisticated form of buffer overflow attack causes the program to execute some exploit code that changes the program's register/memory state, but makes the program return to the original calling function (`test` in this case). The calling function is oblivious to the attack. This style of attack is tricky, though, since you must: 1) get machine code onto the stack, 2) set the return pointer to the start of this code, and 3) undo any noticeable corruptions made to the stack state.

Your job for this level is to supply an exploit string that will cause `getbuf` to return your cookie back to `test`, rather than the value 1. You can see in the code for `test` that this will cause the



---

program to go “Boom!.” Your exploit code should set your cookie as the return value, restore any corrupted state, push the correct return location on the stack, and execute a `ret` instruction to really return to `test`.

**Some Advice:**

- You can use GDB to get the information you need to construct your exploit string. Set a breakpoint within `getbuf` and run to this breakpoint. Determine parameters such as the saved return address.
- Determining the byte encoding of instruction sequences by hand is tedious and prone to errors. You can let tools do all of the work by writing an assembly code file containing the instructions and data you want to put on the stack. Assemble this file with GCC and disassemble it with `OBJDUMP`. You should be able to get the exact byte sequence that you will type at the prompt. (A brief example of how to do this is included at the end of this writeup.)
- Keep in mind that your exploit string depends on your machine, your compiler, and even your teamid’s cookie. Do all of your work on the machines assigned by your instructor, and make sure you include the proper teamid on the command line to `BUFBOMB`.

Once you complete this level, pause to reflect on what you have accomplished. You caused a program to execute machine code of your own design. You have done so in a sufficiently stealthy way that the program did not realize that anything was amiss.

## Level 4: Nitroglycerin 15 pts

Please note: You’ll need to use the “-n,” command-line flag in order to run this stage.

From one run to another, especially by different users, the exact stack positions used by a given procedure will vary. One reason for this variation is that the values of all environment variables are placed near the base of the stack when a program starts executing. Environment variables are stored as strings, requiring different amounts of storage depending on their values. Thus, the stack space allocated for a given user depends on the settings of his or her environment variables. Stack positions also differ when running a program under GDB, since GDB uses stack space for some of its own state. Lastly, modern versions of Linux deliberate randomize the location of the stack from run to run to make the job of attackers seeking to exploit buffer overflow vulnerabilities such as the one contained in this bomb even harder.

In the code that calls `getbuf`, we have incorporated features that stabilize the stack, so that the position of `getbuf`’s stack frame will be consistent between runs. This made it possible for you to write an exploit string knowing the exact starting address of `buf`. If you tried to use such an exploit on a normal program, you would find that it works some times, but it causes segmentation faults at other times. Hence the name “dynamite”—an explosive developed by Alfred Nobel that contains stabilizing elements to make it less prone to unexpected explosions.

---

For this level, we have gone the opposite direction, making the stack positions even less stable than they normally are. Hence the name “nitroglycerin”—an explosive that is notoriously unstable.

When you run `BUFBOMB` with the command line flag “-n,” it will run in “Nitro” mode. Rather than calling the function `getbuf`, the program calls a slightly different function `getbufn`:

```
int getbufn()
{
    char buf[KABOOM_BUFFER_SIZE];
    Gets(buf);
    return 1;
}
```

This function is similar to `getbuf`, except that it has a buffer of 512 characters. You will need this additional space to create a reliable exploit. The code that calls `getbufn` first allocates a random amount of storage on the stack (using library function `alloca`) that ranges between 0 and 255 bytes. Thus, if you were to sample the value of `%ebp` during two successive executions of `getbufn`, you would find they differ by as much as  $\pm 127$ .

In addition, when run in Nitro mode, `BUFBOMB` requires you to supply your string 5 times, and it will execute `getbufn` 5 times, each with a different stack offset. Your exploit string must make it return your cookie each of these times.

Your task is identical to the task for the Dynamite level. Once again, your job for this level is to supply an exploit string that will cause `getbufn` to return your cookie back to test, rather than the value 1. You can see in the code for test that this will cause the program to go “KABOOM!.” Your exploit code should set your cookie as the return value, restore any corrupted state, push the correct return location on the stack, and execute a `ret` instruction to really return to `testn`.

#### Some Advice:

- You can use the program `HEX2RAW` to send multiple copies of your exploit string. If you have a single copy in the file `exploit.txt`, then you can use the following command:

```
unix> cat exploit.txt | ./hex2raw -n | ./bufbomb -n -u rnikola+parang
```

You must use the same string for all 5 executions of `getbufn`. Otherwise it will fail the testing code used by our grading server.

- The trick is to make use of the `nop` instruction. It is encoded with a single byte (code `0x90`). It may be useful to read about “nop sleds” on page 262 of the CS:APP2e textbook.

## Logistical Notes

Handin occurs to the grading server whenever you correctly solve a level *and* use the `-s` option. Upon receiving your solution, the server will validate your string and update the Buffer Lab

---

scoreboard Web page, which you can view by pointing your Web browser at `http://courses.cs.vt.edu/~cs3214/fall2011/buflab/buflab-scoreboard.html`

You should be sure to check this page after your submission to make sure your string has been validated. (If you really solved the level, your string *should* be valid.)

Note that each level is graded individually. You do not need to do them in the specified order, but you will get credit only for the levels for which the server receives a valid message. You can check the Buffer Lab scoreboard to see how far you've gotten.

The grading server creates the scoreboard by using the latest results it has for each phase.

Good luck and have fun!

## Generating Byte Codes

Using GCC as an assembler and OBJDUMP as a disassembler makes it convenient to generate the byte codes for instruction sequences. For example, suppose we write a file `example.S` containing the following assembly code:

```
# Example of hand-generated assembly code

    push $0xabcdef          # Push value onto stack
    add  $17,%eax           # Add 17 to %eax
    .align 4                # Following will be aligned on multiple of 4
    .long 0xfedcba98        # A 4-byte constant
```

The code can contain a mixture of instructions and data. Anything to the right of a '#' character is a comment.

We can now assemble and disassemble this file:

```
unix> gcc -m32 -c example.S
unix> objdump -d example.o > example.d
```

The generated file `example.d` contains the following lines

```
0: 68 ef cd ab 00          push    $0xabcdef
5: 83 c0 11                add     $0x11,%eax
8: 98                      cwtl
9: ba                     .byte 0xba
a: dc fe                  fdivr   %st,%st(6)
```

Each line shows a single instruction. The number on the left indicates the starting address (starting with 0), while the hex digits after the ':' character indicate the byte codes for the instruction. Thus, we can see that the instruction `push $0xABCDEF` has hex-formatted byte code `68 ef cd ab 00`.

---

Starting at address 8, the disassembler gets confused. It tries to interpret the bytes in the file `example.o` as instructions, but these bytes actually correspond to data. Note, however, that if we read off the 4 bytes starting at address 8 we get: `98 ba dc fe`. This is a byte-reversed version of the data word `0xFEDCBA98`. This byte reversal represents the proper way to supply the bytes as a string, since a little endian machine lists the least significant byte first.

Finally, we can read off the byte sequence for our code as:

```
68 ef cd ab 00 83 c0 11 98 ba dc fe
```

This string can then be passed through `HEX2RAW` to generate a proper input string we can give to `BUFBOMB`. Alternatively, we can edit `example.d` to look like this:

```
68 ef cd ab 00 /* push    $0xabcdef */
83 c0 11 /* add      $0x11,%eax */
98
ba dc fe
```

which is also a valid input we can pass through `HEX2RAW` before sending to `BUFBOMB`.